

Tellog PR-32A/32iA

WIRELESS BATTERY-POWERED PRESSURE RTU WITH IMPULSE MONITORING OPTION



GAS SYSTEM PRESSURE AND LEVEL MONITORING WITH OPTIONAL TRANSIENT CAPTURE WAVEFORM

The Tellog PR-32A and Tellog PR-32iA are versatile instruments intended to monitor gas system pressures. When you combine the Tellog PR-32A series with a Trimble software option, you have a powerful system of wireless gas infrastructure monitoring that is consistently delivering real-time data from the field straight to your desktop.

Imagine... all your data on one platform straight to your computer screen.

In addition to performing the measurement and recording functions of the Tellog PR-32A, the impulse recording option feature of the Tellog PR-32iA units stores the waveform of captured pressure transient waves detected on the monitored network. The Tellog PR-32iA can store up to 125 events of variable duration that may occur over many months of on-site monitoring, recording up to a maximum of 2.5 minutes of transient data at 256 samples/second.

Wireless Communication

The power of every Tellog 32 series recorder from Trimble Tellog is wireless data transfer capability. Using cellular technology enables unmanned monitoring of remote sites as well as instant updates and alarm notifications. The Tellog PR-32A/32iA series uses a low power, LTE/Cat 1 cellular communication modem certified on Verizon Wireless.

Collecting Data

The Tellog PR-32A/32iA series may be configured to call its host application on a schedule (e.g. once per day; every four hours, etc.) and/or in response to site alarm conditions (e.g. in response to a high level event). The recorder can sample the pressure sensor up to four times/second (Tellog PR-32A) or up to 256 times/second (Tellog PR-32iA). Data may be stored in the recorder at user defined intervals (e.g. five minutes, one minute, etc.) without concern for data loss because the recorder will store up to 82,000 values, depending on input type, before overwriting the oldest data.

Packaging

The cellular modem, antenna, process signal conditioning, data recorder and battery are in a small IP68 rated Nema 6P enclosure for a combined weight of 2.5 pounds and measuring 4"L x 4"W x 3"H [102 mm L x 102 mm W x 76 mm H].

Battery Powered

The Tellog PR-32A and Tellog PR-32iA recorders use a user replaceable Tellog BP-4 lithium battery pack. At one call per day the battery pack will last up to five years on a PR-32A RTU. The battery life with a PR-32iA depends on the sampling resolution chosen in addition to the call schedule (see table below for examples). With user configurable call and sampling rates, you get to choose the best configuration for your application.

Software Support

Trimble Tellog wireless recorders are compatible with all Trimble software applications, including Trimble Unity, Tellog Online (cloud), Tellog Enterprise and Tellogers for Windows application software. This ensures that gas utilities have a complete solution addressing all their remote monitoring requirements delivered in a manner that suits each individual utility's operations and IT needs.

Applications

- ▶ Gas system pressure monitoring
- ▶ Level monitoring
- ▶ High speed sampling to 256 samples/second

Benefits

- ▶ Improve asset performance, reduce leakage and pipeline failures
- ▶ Monitor and optimize gas and site operations and compliance
- ▶ Real-time situational awareness of high/low level events
- ▶ Battery operated

Features

- ▶ Wireless communication via cellular (LTE)
- ▶ Alarm notification
- ▶ Time stamped events
- ▶ Automatic barometric pressure correction
- ▶ Integral antenna
- ▶ User programmable
- ▶ IP68 Rating

Telog PR-32A/32iA SPECIFICATIONS

RECORDER MODEL: Telog PR-32A and Telog PR-32iA

Type Single channel pressure recorder

Measurement

Resolution	12 bits (0.025%)
Accuracy	±0.075% of full scale at 73 °F ±40 ppm/°F

Temperature range 40 °F to +149 °F [4 °C to 65 °C]

NOTE: For applications below this operating range please contact your Trimble Telog support team.

Recording with PR-32 (no impulse option included)

Sample Rate	4 per second to 1 per 8 hours; programmable
Clock Accuracy	0.01%
Memory Size	31,000 data values
Storage Method	Wrap around (first-in; first-out)

Recording with PR-32i (with impulse option included and on)

Note: When using PR-32i which includes the impulse option, the normal mode specified above will operate whether the impulse mode is on or off.

Data Recorded	Normal mode interval data plus transient event waveforms
Transient Trigger	Pressure rate-of-change; either positive or negative; user configurable
Impulse Memory	Up to 100 transient events to a maximum of 37,000 samples after which new data will overwrite oldest data.

Communication

Local RS-232	4 pin circular connector rated IP-67 Auto-selected baud rate to 19.2K
Cellular	Internal Telog WM2/L1 cellular modem LTE Category 1 certified Verizon Wireless

Battery

Battery Life	Up to 2800 data calls to host computer
Examples:	Call Frequency Sampling Frequency Battery Life
PR-32A	1/day 1/second 5 years
PR-32iA	1/day 4/second 5 years
PR-32iA	1/day 128/second 2 years
PR-32iA	1/day 256/second 1 year

(@ medium to excellent signal strength)

Enclosure

Size	4"L x 4"W x 3"H [102 mm L x 102 mm W x 76 mm H]
Weight	2.5 lbs. [1.2 kg]
Weight	2 lbs [0.9 kg]
Material	Polycarbonate

Environmental

Temperature 40 °F to 158 °F [4 °C to 70 °C]

Note: For applications below this operating range please contact your Trimble Telog support team.

Rating NEMA 6P (IP68)

Support Software

S-3PC	Telogers for Windows® 6.51 or later
S-3EP	Telog® Enterprise 6.51 or later
DHS-Service	Telog Online
TW-UNITY	Trimble Unity

SENSOR SPECIFICATIONS

PR-32A Sensor

Model	PT-DS
Type	Strain gauge pressure sensor
Range	Selectable 5,10,30,100,300 PSIG and 1000 PSI
Accuracy over the calibrated temperature range including zero and span setting and the effects of non-linearity, hysteresis and repeatability	0.25% FS
Cable	Vented Polyurethane 0.225" diameter [5.715 mm]
Pressure Over Range	2x full scale with negligible calibration change 4x containment pressure up to 2900 psi max

Temperature

Range	25 °F to 140 °F [-3.8 °C to 60 °C]
Temperature Effect	±0.01%/°F (32 °F to 90 °F)

PR-32iA Sensor

Model	PT-30b
Type	Strain gauge pressure sensor
Range	Selectable 200, 300, 500 PSIG
Accuracy	
Non-linearity	±0.15% of span; BFSL
Repeatability	±0.03% of span; BFSL
Hysteresis	±0.03% of span; BFSL

Cable

Pressure Over Range	Vented Polyurethane 0.310" diameter [7.87mm] 4x full scale with negligible calibration change 6x containment pressure up to 2900psi max
----------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------

Temperature

Range	25 °F to 140 °F [-3.8 °C to 60 °C]
Temperature Effect	±0.01%/°F (32 °F to 90 °F)

Physical

Pressure Fitting	1/4" NPT female
Environmental	Submersible to NEMA 6P (IP-68)
Sensor Length	4.5" [114 mm]
Sensor Diameter (max)	1.0" [25.5 mm]
Sensor Body Material	316 stainless steel
Cable Weight	0.027 lbs./ft

Specifications within this brochure are subject to change without notification.
The PR-32iA is covered by U.S. Pat. No. 7,219,553 and 7,357,034.

© 2019, Telog, A Trimble Company. All rights reserved. Telog is a registered trademark and Telogers is a trademark of Telog, A Trimble Company. Trimble and the Globe & Triangle logo are trademarks of Trimble Inc., registered in the United States and in other countries. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Verizon Wireless is a trademark of Verizon Trademark Services. All other trademarks are the property of their respective owners. PN 022544-019 (Apr 26 2019)



IRVINE OFFICE, CALIFORNIA, USA
18500 Von Karman Avenue,
Suite 260, Irvine, CA 92612
+1 (949) 892-6120

CORK OFFICE, IRELAND
R.o.W: Trimble Navigation Limited
NSC Campus, Mahon, Cork Ireland
+353 21 230 9328

TELOG (ROCHESTER OFFICE),
NEW YORK, USA
830 Canning Parkway
Victor, New York 14564
+1 (585) 742-3000

TrimbleWater_ContactUs@trimble.com
www.trimblewater.com